




Notes:

- Radiation patterns and gain values at the table are including the effect of supporting pole
- Null fill, beam tilt, harness & feeder losses NOT INCLUDED
- Wind load & weight figures without considering cables, splitters & hardware

Electrical Specifications

Frequency Range	87.5 -108 MHz
Peak gain	0 dB (ref. □ / 2 dipole, free space) 1.75 dB (ref. □ / 2 dipole, with pole)
3 db beam width	E-plane: 75° H-plane: 220°
Polarization	Vertical
Impedance	50 Ohm
VSWR	≤ 1.3:1
Maximun power handling	3 kW
Connector type	DIN 7/16
Pressurization	Non pressurized

Mechanical & Environmental Specifications

Materials:	Dipole Isolators	Stainless steel PTFE
Dimensions (W x D x H)		85 x 1000 x 1340 mm
Maximun wind speed		200 km/h
Wind load		165 N (@ 160 km /h)
Weight		9 kg
Clamp Type		To Ø 60 – 80 mm pipe
Vertical spacing		0,8 0,9 typical
Grounding		DC grounded
Temperature range		-40°C to +80°C
Humidity		100%

Antenna System Characteristics

Number of Bays	Number ant. Per bay	Peak gain (dbd)	Weight (kg)	Wind load (@160 km/h)	System height (mm)
1	1	1.8	10	0,17 kN	1340
2	1	4.8	20	0,34 kN	3949
4	1	7.8	40	0,68 kN	9166
6	1	9.5	60	1,02 kN	14383
8	1	10.8	80	1,36 kN	19601
10	1	11.8	100	1,70 kN	24821
12	1	12.6	120	2,04 kN	30039

EUROTEL BROADCAST S.L.